

Lockable Window Restrictors

The Royal Association for the Prevention of Accidents report that each year 4,000 children under the age of 15 fall out of a window. We have recently launched a simple, affordable and very effective solution to this in the form of the UAP Window Restrictor.

Available in three finishes

Withstand forces



20cm long restrictor restricts opening to under 100mm

Comes with one universal key

Our lockable window restrictor can be fitted to any window in minutes; it has a 20cm long cable, which when installed correctly will limit the opening of the window to under 100mm. Not only will this prevent children from being able to fit through the gap, but it also allows enough air to circulate around a room.

To comply with the EN 13126-5:2011 + A1:2014 test standard, the restrictor(s) must be fitted so that the total opening of the whole length of the window opening is less than 89mm when using as a child safety product, and 100mm for other requirements.

The window restrictor is designed to take a minimum of a 35kg load when it is pushed open. The window may need to have multiple restrictors fitted to achieve this requirement. There is no minimum or maximum dimension for which window can be used as long as the window opening is restricted to 89mm or 100mm.

The window restrictor is lockable, and can be unlocked using a key if necessary, and the window will then be able to be opened fully. Due to this reason, it is possible to fit the UAP lockable window restrictor on fire escape windows, provided that the user keeps the key within easy reach.

Can be used on all types of windows and doors including uPVC, aluminium, wooden and metal profiles





Lockable Window Restrictors

Testing Standards	Internally tested to relevant parts of EN16281:2013. Exceeds strength requirements withstanding a minimum force of 1350N
Materials	Covers and cable cover – plastic Cable – steel & crimped metal part Screws – Steel Fixing points – Steel Key – Steel
Finishes	White Brown (coming soon)
Dimensions	Cable Length - 200mm Main fixing lock - 65mm x 19mm Screws - 4mm x 30mm
Profile Compatibility	Suitable for all windows and doors including uPVC, aluminium, wooden and metal profiles.
Guarantee	1 Year





