

DOOR STAY

The fantastic UAP Door Stay has now been tested to withstand gale force winds, making it in our opinion the best product on the market!

The restrictor limits door opening to a preset position, or to a maximum of 90 degrees, and includes an easy-to-fit eurogroove and bracket to frame. Our Door Stay is perfectly suitable for all major uPVC profiles, and measures 335mm in length. It can withstand literally thousands upon thousands of openings without becoming damaged, and does not become affected by daily wear and tear! Additionally, a carefully constructed slider contains special friction screws to hold the door open in mild wind conditions, so that it remains stable and steady.



Features Include:

- Independently tested to withstand gale force winds!
- Suitable for ALL major UPVC profiles
- Easy to fit Euro groove and bracket to frame
- Restrictor limits door opening to a preset position (or to a maximum of 90 degrees)
- Modern and innovative design
- Slider contains friction screws to hold the door open in mild wind conditions
- Can withstand thousands of openings
- Door stay made with a steel arm
- 335mm in length

DOOR STAY

Product Code

DOORSTAY-UNIVERSAL

Product Guarantee

We guarantee the products and finish against the following;

Surface Coating Failure

We guarantee that the door stay will not tarnish for a period of 2 years subject to;

1. The door stays are applied internally to a door, window frame or door panel and no item of door furniture on the door, window frame or door panel are sealed or fixed using any form of silicone sealant or the like
2. The door stays are fixed internally and correctly using the correct fixings and are not scratched or damaged at any time during the installation process or thereafter
3. The door stays are cleaned monthly with a moist cloth and not with any form of cleaning agents
4. No claim will be accepted for any door stay that is scratched or mutilated or fitted incorrectly

Mechanical Failure

We guarantee that the above products will not fail mechanically during the 2 year guarantee period subject to the conditions outlined above.



Position the UAP Door Stay onto the head of the door sash 105mm from the sash rebate corner on the hinge side.



Position the striker plate behind the bead groove on the outer frame 45mm from the corner and screw into position.



After hanging the sash, clip the arm of the UAP Door Stay into the striker plate.

Note: Should additional friction be required simply tighten the hexagonal screw within the UAP Door Stay