

XL is available in a range of lock configurations and can be used with either one piece or individual keep sets. The XL's attractive silver finish is also corrosion resistant to neutral salt spray in excess of BSEN1670 Grade 4, giving peace of mind to hard pressed fabricators and consumers.

Various 3 hook XL lock centres are available, with either 2 or 4 roller compression cams.

Other locks available include XLSL slave lock, XL4R centre hook, latch and 4 roller or XL2R2M centre hook, latch, 2 rollers and 2 mushroom cams.

PAS2424 tested

One piece or individual keeps

Three opposing steel hooks and two steel anti lift bolts

Two or four roller cams

Easily reversible latch as standard

Dual, single or split spindle options

Extendable top and bottom as standard

Latch hold back snib on lock faceplate

For use on PVCu doors



Technical Data

Corrosion Resistance

BSEN1670 Grade 4 (240 hours)

Cyclic Operation

Cycles Tested to 200,000 cycles

Materials

Top and Bottom Hook

Chrome plated A3 hardened cast steel

Anti Lift Bolts

Chrome plated A3 hardened cast steel

Centre Hook

Dacromet coated A3 sintered steel

Faceplate and Gearbox

Mild steel, zinc and clear passivated

Roller Cams

Mild steel, zinc and clear passivated

For maximum security the XL Lock can be used with the Kinetica 3 star BSI Kitemarked TS007 cylinder.



The XL was designed from the outset to offer maximum security and reliability. XL features three hooks, two steel anti lift bolts and the option of either two or four roller cams for compression and smooth operation. Every

XL lock is extendable top and bottom for maximum flexibility and combined with Fullex high security shoot bolts, the XL French door system is fully capable of meeting PAS24 requirements. The XL 3 hook also forms the heart of the CE marked XL Exodus Panic exit system and utilises the same lock preparation.

518mm Centres:

Faceplate = 2200mm x 16mm (Silver Passivated)

Product Code	Spindle	Backset Size	Handle Backplate	Handle Centres	No of Hooks	Hook Direction	No of Deadbolts	No of Anti-Lift Bolts	No of Rollers	No of Mushrooms
XL32R518	Dual	35mm	243mm	92mm or 92/62mm	3	Opposing	0	2	2	0
XL32R518SP	Single	35mm	243mm or 219mm	92mm	3	Opposing	0	2	2	0
XL32R518S/5	Split	35mm	243mm or 219mm	92mm	3	Opposing	0	2	2	0

650mm Centres:

Faceplate = 2200mm x 16mm (Silver Passivated)

Product Code	Spindle	Backset Size	Handle Backplate	Handle Centres	No of Hooks	Hook Direction	No of Deadbolts	No of Anti-Lift Bolts	No of Rollers	No of Mushrooms
XL32R650	Dual	35mm	243mm	92mm or 92/62mm	3	Opposing	0	2	2	0
XL32R650SP	Single	35mm	243mm or 219mm	92mm	3	Opposing	0	2	2	0
XL32R650S/5	Split	35mm	243mm or 219mm	92mm	3	Opposing	0	2	2	0

650mm Centres:

Faceplate = 2200mm x 16mm (Silver Passivated)

Product Code	Spindle	Backset Size	Handle Backplate	Handle Centres	No of Hooks	Hook Direction	No of Deadbolts	No of Anti-Lift Bolts	No of Rollers	No of Mushrooms
XL32R7474	Dual	35mm	243mm	92mm or 92/62mm	3	Opposing	0	2	4	0
XL32R7474SP	Single	35mm	243mm or 219mm	92mm	3	Opposing	0	2	4	0
XL32R57474S/5	Split	35mm	243mm or 219mm	92mm	3	Opposing	0	2	4	0

XL Slave Lock:

Faceplate = 2200mm x 16mm (Silver Passivated)

Product Code	Spindle	Backset Size	Handle Backplate	Handle Centres	No of Hooks	Hook Direction	No of Deadbolts	No of Anti-Lift Bolts	No of Rollers	No of Mushrooms
XLSL	Single	35mm	243mm or 219mm	92mm	0	-	0	0	0	0

Product Code	Spindle	Backset Size	Handle Backplate	Handle Centres	No of Hooks	Hook Direction	No of Deadbolts	No of Anti-Lift Bolts	No of Rollers	No of Mushrooms
XL2R2M	Dual	35mm	243mm	92mm or 92/62mm	0	-	0	0	2	2
XL4R	Single	35mm	243mm or 219mm	92mm	0	-	0	0	4	0
XL4RPRO	Dual	35mm	243mm or 219mm	92mm	0	-	0	0	4	0