

Gemini makes composite or timber double doors simple. With both master and slave lock mounted on hard wearing aluminium extrusions that mount on the door edge, fitting is simple.

The 3 deadbolt master lock interlocks with the slave, locking the 14mm wide top and bottom shootbolts in place achieving both PAS24 and Secured by Design security.

PAS24 tested

Tapered top and bottom deadbolts offer high security and compression

Double operating handle option or dummy external handle to slave

Split spindle option for use on front door applications

304 grade stainless steel faceplate and slave lock for high corrosion resistance



Technical Data

Corrosion Resistance

BSEN1670 Grade 5 (480 hours)

Cyclic Operation

Cycles Tested to 100,000 cycles

Materials

Top and Bottom Hook

CZ122 brass stamping

Deadbolt

CZ122 brass stamping

Faceplate

304 austenitic stainless steel

Gearbox

Dacromet coated die cast zinc

Carrier Extrusions

White and black powder coated or polished anodised silver and gold

For maximum security the Gemini can be used with the Kinetica 3 star BSI Kitemarked TS007 cylinder.



With a range of hardwearing and attractively finished extrusions available for 44mm composite door and with a direct fit option for Timber doors, Fullex Gemini is adaptable and secure.



Right Hand Opening Out | Left Hand Opening In

Product Code	Finish
GM100-10-2150	White Painted
GM100-40-2150	Silver Anodised
GM100-80-2150	Gold Anodised

Right Hand Opening In | Left Hand Opening Out

Product Code	Finish
GM102-10-2150	White Painted
GM102-40-2150	Silver Anodised
GM102-80-2150	Gold Anodised